



FORM
6
Rev
05/18

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
Document Number: 401703926			
Date Received: 07/16/2018			

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set.
A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

OGCC Operator Number: 47120 Contact Name: CHERYL LIGHT
 Name of Operator: KERR MCGEE OIL & GAS ONSHORE LP Phone: (720) 929-6461
 Address: P O BOX 173779 Fax: (720) 929-7461
 City: DENVER State: CO Zip: 80217- Email: cheryl.light@anadarko.com

For "Intent" 24 hour notice required, Name: Carlile, Craig Tel: (970) 629-8279
COGCC contact: Email: craig.carlile@state.co.us

API Number 05-123-19165-00
 Well Name: HSR-HEINTZELMAN Well Number: 16-32
 Location: QtrQtr: SESE Section: 32 Township: 3N Range: 67W Meridian: 6
 County: WELD Federal, Indian or State Lease Number: _____
 Field Name: WATTENBERG Field Number: 90750

Notice of Intent to Abandon Subsequent Report of Abandonment

Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.176394 Longitude: -104.906000
 GPS Data:
 Date of Measurement: 10/21/2008 PDOP Reading: 2.3 GPS Instrument Operator's Name: Cody Mattson
 Reason for Abandonment: Dry Production Sub-economic Mechanical Problems
 Other _____
 Casing to be pulled: Yes No Estimated Depth: 905
 Fish in Hole: Yes No If yes, explain details below
 Wellbore has Uncemented Casing leaks: Yes No If yes, explain details below
 Details: _____

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
CODELL	7314	7319			
J SAND	7746	7780			
NIOBRARA	7116	7118			

Total: 3 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Weight Per Foot	Setting Depth	Sacks Cement	Cement Bot	Cement Top	Status
SURF	12+1/4	8+5/8	24	634	445	634	0	VISU
1ST	7+7/8	4+1/2	11.6	7,475	170	7,475	6,616	CBL
S.C. 1.1				4,628	340	4,628	3,840	CBL
1ST LINER	3+7/8	2+7/8	6.5	7,903	30	7,903	7,382	CBL

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 7680 with 2 sacks cmt on top. CIBP #2: Depth 7030 with 25 sacks cmt on top.
 CIBP #3: Depth 3970 with 2 sacks cmt on top. CIBP #4: Depth 80 with 25 sacks cmt on top.
 CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set 25 sks cmt from 7030 ft. to 6680 ft. Plug Type: CASING Plug Tagged:
 Set 15 sks cmt from 3460 ft. to 3240 ft. Plug Type: CASING Plug Tagged:
 Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
 Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:
 Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged:

Perforate and squeeze at 3800 ft. with 95 sacks. Leave at least 100 ft. in casing 3460 CICR Depth
 Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
 Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth
 (Cast Iron Cement Retainer Depth)

Set 240 sacks half in. half out surface casing from 1005 ft. to 584 ft. Plug Tagged:
 Set 25 sacks at surface
 Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: Yes No
 Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: _____ ft. _____ inch casing Plugging Date: _____
 of _____
 *Wireline Contractor: _____ *Cementing Contractor: _____
 Type of Cement and Additives Used: _____
 Flowline/Pipeline has been abandoned per Rule 1105 Yes No *ATTACH JOB SUMMARY

Technical Detail/Comments:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: CHERYL LIGHT
 Title: Staff Regulatory Analyst Date: 7/16/2018 Email: DJREGULATORY@ANADARKO.COM

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: McCoy, Diane Date: 8/2/2018

CONDITIONS OF APPROVAL, IF ANY: _____ Expiration Date: 2/1/2019

COA Type	Description
	<p>1) Provide 48 hour notice of plugging MIRU via electronic Form 42.</p> <p>2) Properly abandon on-location flowlines per Rule 1105. File electronic Form 42 once abandonment complete. Within 30 days of an operator completing abandonment requirements for an off-location flowline or crude oil transfer line the operator must submit a Flowline Report, Form 44.</p> <p>3) Operator shall implement measures to control unnecessary and excessive venting, to protect the health and safety of the public, and to ensure that vapors and odors from well plugging operations do not constitute a nuisance or hazard to public welfare.</p> <p>4) Please submit gyro survey data with Form 6 Subsequent Report of Abandonment.</p> <p>5) After pumping squeeze, shut down and shut well in at minimum 8 hours; verify gas migration has been eliminated. If evidence of gas migration or pressure remains contact COGCC Engineer for an update to plugging orders.</p>
	<p>Prior to starting plugging operations a bradenhead test shall be performed if there has not been a reported bradenhead test within the 60 days immediately preceding the start of plugging operations.</p> <p>1) If, before opening the bradenhead valve, the beginning pressure is greater than 25 psi, sampling is required.</p> <p>2) If pressure remains at the conclusion of the test, or if any liquids were present during the test, sampling is required.</p> <p>The Form 17 shall be submitted within 10 days of the test. Sampling shall comply with Operator Guidance - Bradenhead Testing and Reporting Instructions. If samples are collected, copies of all final laboratory analytical results shall be provided to the COGCC within three (3) months of collecting the samples.</p>

Attachment Check List

Att Doc Num	Name
401703926	WELL ABANDONMENT REPORT (INTENT)
401704051	PROPOSED PLUGGING PROCEDURE
401704052	WELLBORE DIAGRAM
401723007	FORM 6 INTENT SUBMITTED

Total Attach: 4 Files

General Comments

User Group	Comment	Comment Date
Engineer	<p>Production records indicate this well has been SI since November 2016. All shut-in wells must pass a mechanical integrity test or be plugged and abandoned within two years of the initial shut-in date, this form 6 intent does not extend that due date.</p> <p>Added CIBP at 3970' shown on wellbore diagram to this form.</p> <p>If there is still pressure or evidence of fluid migration after pumping squeeze, do not pump the production casing stub plug and surface casing shoe plug as one plug. Contact COGCC engineering for an update to the plugging procedure.</p>	08/02/2018
Well File Verification	Pass	07/20/2018
Permit	Pass	07/19/2018

Total: 3 comment(s)



THE PLUG & ABANDONMENT PROCESS



When a well is no longer economically producing oil and natural gas, the well is evaluated for retirement and will undergo a process called 'plug and abandonment,' or P&A as it is often called.

To retire, or P&A, a well, the operator must submit a plug and abandonment plan to the state regulatory authority, the Colorado Oil and Gas Conservation Commission (COGCC) for approval.

Once the plan is approved by the COGCC, the operator is required to inform the municipality where the well is located. Operators also communicate with surface land and mineral owners and surrounding neighbors regarding the retirement of the well.

How a Well is Retired



1

A workover rig arrives on-site. While the rig is on location, the well will be plugged per the plan approved by the COGCC. Cement is pumped into the well to cover and isolate the zones that produce oil and natural gas.



2

When the plugging operation is complete, the workover rig moves off the location, the well head is removed and the associated flowlines are excavated. Associated surface equipment (tanks, separators, etc.) may also be removed if it is not serving other active wells in the area.



3

The remaining portion of the well is cut a minimum of seven feet below the surface and an identifying marker is welded to the top of the plugged wellbore.



4

A final report is submitted to the COGCC to certify the wellbore has been plugged in accordance with the regulatory requirements.



5

The site is reclaimed, or restored, to match the existing landscape.